



Manual GL-4 90

Manual Transmission Fluid

Description

Castrol Manual GL-4 90 may be used in applications where API GL-4 performance is required.

Advantages

- Good thermal stability protects against deposit formation and oil thickening maintaining the life and performance of lubricant and transmission.
- Good antiwear and load carrying characteristics extend the life of components. Improved low temperature protection and gear shifts compared to monograde products

Typical Characteristics

Name	Method	Units	Manual GL-4 90
Density @ 15C, Relative	ASTM D4052	g/ml	0.895
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	16.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	187
Viscosity Index	ASTM D2270	None	96
Pour Point	ASTM D97	°C	-6
Flash Point, COC	ISO 2592	°C	282

Product Performance Claims

API GL-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Manual GL-4 90

14 May 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Singapore Pte. Limited (202034037D), 7 Straits View, Marina One East Tower, #26-01, Singapore 018936

Phone No : +65-6335 3000

www.castrol.com