

# SAFETY DATA SHEET



Optigear BM 320

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** Optigear BM 320  
**SDS #** 450753  
**Code** 450753-US03

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** Gear lubricant  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Manufacturer** BP Lubricants USA Inc.  
1500 Valley Road  
Wayne, NJ 07470  
Telephone: +1-888-CASTROL

**Supplier** PAN AMERICAN ENERGY S.L., SUCURSAL  
ARGENTINA AV. LEANDRO N. ALEM 1180  
PISO 11 – C1001AAT  
CIUDAD AUTÓNOMA DE BUENOS AIRES.

Consultas Técnicas 0800-888-8088

**EMERGENCY HEALTH INFORMATION:** TELÉFONO PARA EMERGENCIAS (24 HORAS) CIQUIME: 0800-222-2933  
+1-800-424-9300 (CHEMTREC USA)  
+1-703-527-3887 (CHEMTREC outside the US)

**EMERGENCY TELEPHONE NUMBER**

## SECTION 2: Hazards identification

**Classification of the substance or mixture** SKIN IRRITATION - Category 3  
SKIN SENSITIZATION - Category 1  
AQUATIC HAZARD (ACUTE) - Category 3  
AQUATIC HAZARD (LONG-TERM) - Category 3

### GHS label elements

**Hazard pictograms**



**Signal word** Warning

**Hazard statements** H316 - Causes mild skin irritation.  
H317 - May cause an allergic skin reaction.  
H412 - Harmful to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** P280 - Wear protective gloves.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapor.  
P272 - Contaminated work clothing should not be allowed out of the workplace.

**Response** P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
P333 + P313 - If skin irritation or rash occurs: Get medical attention.

**Product name** Optigear BM 320

**Product code** 450753-US03

**Page:** 1/11

**Date of issue** 03/22/2022.

**Format** Argentina

**Language** ENGLISH

**Version** 6.01

**(AR)**

**(ENGLISH)**

## SECTION 2: Hazards identification

**Storage** Not applicable.

**Disposal** P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** None known.

## SECTION 3: Composition/information on ingredients

**Substance/mixture** Mixture

Highly refined mineral oil and additives.

**Other means of identification** Not available.

Ingredient name	CAS number	%
Residual oils (petroleum), solvent-dewaxed	64742-62-7	≥50 - ≤75
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	≥25 - ≤50
Residual oils (petroleum), solvent-dewaxed	64742-62-7	≤3
Zinc dialkyl dithiophosphate	68457-79-4	≤2.4
Sulfonic acids, petroleum, magnesium salts	61789-87-5	≤3
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	Proprietary	≤1.9
maleic anhydride	108-31-6	≤0.1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### Description of necessary first aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
<b>Skin contact</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. In the event of any complaints or symptoms, avoid further exposure. Get medical attention.
<b>Inhalation</b>	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.
<b>Protection of first-aiders</b>	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

<b>Product name</b> Optigear BM 320	<b>Product code</b> 450753-US03	<b>Page:</b> 2/11
<b>Date of issue</b> 03/22/2022.	<b>Format</b> Argentina	<b>Language</b> ENGLISH
<b>Version</b> 6.01	<b>(AR)</b>	<b>(ENGLISH)</b>

## SECTION 4: First aid measures

### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### Specific treatments

No specific treatment.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media

Use foam or all-purpose dry chemical to extinguish.

#### Unsuitable extinguishing media

Do not use water jet.

### Specific hazards arising from the chemical

Swarf fires - Neat metal working oils may fume, thermally decompose or ignite if they come into contact with red hot swarf. To minimise the generation of red hot swarf ensure that a sufficient flow of oil is correctly directed to the cutting edge of the tool to flood it throughout cutting operations. As an additional precaution swarf should be regularly cleared from the immediate area to prevent the risk of fire. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects.

### Hazardous thermal decomposition products

Combustion products may include the following:  
metal oxide/oxides  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)  
nitrogen oxides (NO, NO<sub>2</sub> etc.)

### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

#### For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

### Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Product name** Optigear BM 320

**Product code** 450753-US03

**Page:** 3/11

**Date of issue** 03/22/2022.

**Format** Argentina

**Language** ENGLISH

**Version** 6.01

**(AR)**

**(ENGLISH)**

## SECTION 6: Accidental release measures

### Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

## SECTION 7: Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilled material and runoff with soil and surface waterways. Concentrations of mist, fumes and vapors in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid, as can bacteria, and as a result may induce allergic and other skin reactions, especially if personal hygiene is inadequate.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Residual oils (petroleum), solvent-dewaxed	<b>Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2003 Form: mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 11/2003 Form: mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<b>Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2003 Form: mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/

Product name Optigear BM 320

Product code 450753-US03

Page: 4/11

Date of issue 03/22/2022.

Format Argentina

Language ENGLISH

Version 6.01

(AR)

(ENGLISH)

## SECTION 8: Exposure controls/personal protection

Residual oils (petroleum), solvent-dewaxed

Revised: 11/2003 Form: mist  
**Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).**  
TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 11/2003 Form: mist  
STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 11/2003 Form: mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

Safety glasses with side shields.

#### Skin protection

##### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

##### Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

**Product name** Optigear BM 320

**Product code** 450753-US03

**Page:** 5/11

**Date of issue** 03/22/2022.

**Format** Argentina

**Language** ENGLISH

**Version** 6.01

**(AR)**

**(ENGLISH)**

## SECTION 8: Exposure controls/personal protection

### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m<sup>3</sup>), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m<sup>3</sup>).

Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application.

Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

#### Physical state

Liquid.

#### Color

Brown. [Dark]

#### Odor

Not available.

#### Odor threshold

Not available.

#### pH

Not applicable.

#### Melting point/freezing point

Not available.

#### Boiling point, initial boiling point, and boiling range

Not available.

#### Flash point

Open cup: >200°C (>392°F) [Cleveland]

#### Pour point

-15 °C

#### Evaporation rate

Not available.

#### Flammability

Not applicable. Based on - Physical state

#### Lower and upper explosion limit/flammability limit

Not available.

#### Vapor pressure

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Residual oils (petroleum), solvent-dewaxed	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Residual oils (petroleum), solvent-dewaxed	<0.08	<0.011	ASTM D 5191			
Zinc dialkyl dithiophosphate	0	0	EU A.4	0	0	EU A.4

#### Relative vapor density

Not available.

#### Density

<1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15.6°C

#### Solubility

insoluble in water.

**Product name** Optigear BM 320

**Product code** 450753-US03

**Page:** 6/11

**Date of issue** 03/22/2022.

**Format** Argentina

**Language** ENGLISH

**Version** 6.01

**(AR)**

**(ENGLISH)**

## SECTION 9: Physical and chemical properties

<b>Partition coefficient: n-octanol/water</b>	Not applicable.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Kinematic: 320 mm <sup>2</sup> /s (320 cSt) at 40°C
<b>Particle characteristics</b>	
<b>Median particle size</b>	Not applicable.

## SECTION 10: Stability and reactivity

<b>Reactivity</b>	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
<b>Conditions to avoid</b>	Avoid excessive heat.
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Species	Result	Exposure	Remarks
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	LD50 Dermal	Rat	>2000 mg/kg	-	-
	LD50 Oral	Rat	>2000 mg/kg	-	-
<b>Conclusion/Summary</b>	Not available.				

#### Irritation/Corrosion

Product/ingredient name	Species	Result	Score	Exposure	Observation Conc.	Remarks
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	Rabbit	Skin - Moderate irritant	-	-	-	-
	Rabbit	Eyes - Redness of the conjunctivae	≥2	-	-	-

#### Sensitization

<b>Product name</b> Optigear BM 320	<b>Product code</b> 450753-US03	<b>Page:</b> 7/11
<b>Date of issue</b> 03/22/2022.	<b>Format</b> Argentina	<b>Language</b> ENGLISH
<b>Version</b> 6.01	<b>(AR)</b>	<b>(ENGLISH)</b>

## SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result	Remarks
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	skin	Guinea pig	Sensitizing	-

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
maleic anhydride	Category 1	inhalation	respiratory system

### Information on the likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

### Potential acute health effects

#### Eye contact

No known significant effects or critical hazards.

#### Skin contact

Causes mild skin irritation. Defatting to the skin. May cause an allergic skin reaction.

#### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

#### Ingestion

Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

#### Eye contact

Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

#### Skin contact

Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

#### Inhalation

No specific data.

#### Ingestion

No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

##### Potential immediate effects

Not available.

##### Potential delayed effects

Not available.

#### Long term exposure

##### Potential immediate effects

Not available.

##### Potential delayed effects

Not available.

#### Potential chronic health effects

##### General

No known significant effects or critical hazards.

##### Carcinogenicity

No known significant effects or critical hazards.

##### Mutagenicity

No known significant effects or critical hazards.

##### Teratogenicity

No known significant effects or critical hazards.

##### Developmental effects

No known significant effects or critical hazards.

##### Fertility effects

No known significant effects or critical hazards.

Product name Optigear BM 320

Product code 450753-US03

Page: 8/11

Date of issue 03/22/2022.

Format Argentina

Language ENGLISH

Version 6.01

(AR)

(ENGLISH)



## SECTION 11: Toxicological information

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	179004.66 mg/kg

## SECTION 12: Ecological information

### Toxicity

Product/ingredient name	Species	Test/Result	Exposure	Effects	Remarks
Reaction product of ammonium molybdate and C12-C24-diethoxylated alkylamine (1:5-1:3)	Daphnia	Chronic EC50 6.8 mg/l	48 hours	-	-
<b>Conclusion/Summary</b>	Not available.				
<b>Environmental effects</b>	This material is harmful to aquatic life with long lasting effects.				

### Persistence and degradability

Expected to be biodegradable.

### Bioaccumulative potential

Not available.

### Mobility in soil

<b>Soil/water partition coefficient (K<sub>oc</sub>)</b>	Not available.
<b>Mobility</b>	Non-volatile. Liquid. insoluble in water.

**Other adverse effects** No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

<b>Disposal methods</b>	The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-------------------------	--

<b>Product name</b> Optigear BM 320	<b>Product code</b> 450753-US03	<b>Page:</b> 9/11
<b>Date of issue</b> 03/22/2022.	<b>Format</b> Argentina	<b>Language</b> ENGLISH
<b>Version</b> 6.01	<b>(AR)</b>	<b>(ENGLISH)</b>

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA/ICAO
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

**Special precautions for user** Not available.

**Transport in bulk according to IMO instruments** Not available.

## SECTION 15: Regulatory information

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Other regulations

**Australia inventory (AIIC)** At least one component is not listed.

**Canada inventory** At least one component is not listed in DSL but all such components are listed in NDSL.

**China inventory (IECSC)** All components are listed or exempted.

**Japan inventory (CSCL)** At least one component is not listed.

**Korea inventory (KECI)** At least one component is not listed.

**Philippines inventory (PICCS)** At least one component is not listed.

**Taiwan Chemical Substances Inventory (TCSI)** All components are listed or exempted.

**United States inventory (TSCA 8b)** All components are active or exempted.

**Product name** Optigear BM 320

**Product code** 450753-US03

**Page:** 10/11

**Date of issue** 03/22/2022.

**Format** Argentina

**Language** ENGLISH

**Version** 6.01

**(AR)**

**(ENGLISH)**

## SECTION 15: Regulatory information

### REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

## SECTION 16: Other information

### History

**Date of issue/Date of revision** 03/22/2022.

**Date of previous issue** 11/19/2021.

**Prepared by** Product Stewardship

### Key to abbreviations

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

VOC = Volatile Organic Compound

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

🚩 Indicates information that has changed from previously issued version.

### Notice to reader

*All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.*

*The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.*

*It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.*