SAFETY DATA SHEET



Castrol Transmax Manual V 75W-80

Section 1. Chemical product and company identification

| GHS product identifier | Castrol Transmax Manual V 75W-80 | | | | | |
|--------------------------------|---|--|--|--|--|--|
| Product code | 469686-DE01 | | | | | |
| SDS no. | 469686 | | | | | |
| Relevant identified uses of th | e substance or mixture and uses advised against | | | | | |
| Product use | Manual transmission fluid. For specific application advice see appropriate Technical Data Sheet or consult our company representative. | | | | | |
| Supplier | Setra Lubricants LLC 2 Paveletskaya Square, Bld. 1 115054 Moscow, Russia | | | | | |
| | Tel +7 (495) 961-27-87 Fax +7 (495) 961-27-99 | | | | | |
| EMERGENCY TELEPHONE NUMBER | Carechem: +44 (0) 1235 239 670 (24/7) | | | | | |

Section 2. Hazards identification

| Classification of the substance or mixture | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
|---|--|
| GHS label elements | |
| Signal word | No signal word. |
| Hazard statements | H412 - Harmful to aquatic life with long lasting effects. |
| Precautionary statements | |
| General | P103 - Read label before use. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand. |
| Prevention | P273 - Avoid release to the environment. |
| Response | Not applicable. |
| Storage | Not applicable. |
| Disposal | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Other hazards which do not result in classification | Defatting to the skin. |

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Synthetic base stock. Proprietary performance additives.

| Ingredient name | % | CAS number |
|---|------------------------|------------------------------------|
| 1-Decene, homopolymer, hydrogenated Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, | ≥25 - ≤50 ≥25 - ≤50 | 68037-01-4 68037-01-4 |
| hydrogenated | -2 | Dronvieten |
| Phosphoric acid esters, amine salt Base oil - unspecified | ≤3 ≤3 | Proprietary Varies - See Key to |
| | | abbreviations |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ≤3 | 64742-65-0 |
| Alkenyl amine | ≤0.3 | Confidential. |
| isodecyl methacrylate | ≤0.3 | 29964-84-9 |
| dec-1-ene | ≤0.3 | 872-05-9 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

| Description of necess | ary first aid measures |
|-----------------------|---|
| Inhalation | If inhaled, remove to fresh air. Get medical attention if symptoms occur. |
| Ingestion | Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe. |
| Skin contact | Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. |
| Eye contact | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention. |
| Most important sympt | oms/offects acute and delayed |

Most important symptoms/effects, acute and delayed See Section 11 for more detailed information on health effects and s

| Se | ee S | ection | 11 TOP | more | detalled | Into | rmation | on ne | eaith | enects | and | symp | toms. | |
|----|------|--------|--------|------|----------|------|---------|-------|-------|--------|-----|------|-------|--|
| | | | | | | | | | | | | | | |

| Indication of immediate medi | cal attention and special treatment needed, if necessary |
|------------------------------|--|
| Specific treatments | No specific treatment. |
| Notes to physician | Treatment should in general be symptomatic and directed to relieving any effects. |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

Section 5. Firefighting measures

| Extinguishing media | | | | | | |
|--|---|--|-------------|-----------|--|--|
| Suitable extinguishing media | Use foam or all-purpose dry chemical to extinguish. | | | | | |
| Unsuitable extinguishing media | Do not use water jet. | | | | | |
| Specific hazards arising from the chemical | Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. | | | | | |
| Hazardous thermal decomposition products | | may include the following: O ₂) (carbon monoxide, carbo | on dioxide) | | | |
| Product name Castrol Transma | ax Manual V 75W-80 | Product code | 469686-DE01 | Page: 2/9 | | |
| Version 3.01 Date of issue | 11/24/2020. | Format Russia | Language | ENGLISH | | |
| | | Russia | | (ENGLISH) | | |

Section 5. Firefighting measures

| Special protective equipment for fire-fighters | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. |
|--|--|
| for fire-fighters | there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective actions | Promptly isolate the scene by removing all persons from the vicinity of the incident if |

Section 6. Accidental release measures

| <u>reisonai precautions, protectiv</u> | <u>re equipment and emergency procedures</u> |
|--|--|
| For non-emergency personnel | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Contact emergency personnel. |
| For emergency responders | Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel". |
| Environmental precautions | Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| | |

Methods and material for containment and cleaning up

Small spillStop leak if without risk. Move containers from spill area. Absorb with an inert
material and place in an appropriate waste disposal container. Dispose of via a
licensed waste disposal contractor.Large spillStop leak if without risk. Move containers from spill area. Approach the release
from upwind. Prevent entry into sewers, water courses, basements or confined
areas. Contain and collect spillage with non-combustible, absorbent material e.g.
sand, earth, vermiculite or diatomaceous earth and place in container for disposal
according to local regulations. Contaminated absorbent material may pose the
same hazard as the spilt product. Dispose of via a licensed waste disposal
contractor.

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways. |
|--|---|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures |

| Product name | Castrol Transm | ax Manual V 75W-80 | | Product code | 469686-DE01 | Page: 3/9 |
|--------------|----------------|--------------------|--------|--------------|-------------|-----------|
| Version 3.01 | Date of issue | 11/24/2020. | Format | Russia | Language | ENGLISH |
| | | | | Russia | | (ENGLISH) |

Section 7. Handling and storage

| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use | | | | |
|--|---|--|--|--|--|
| | appropriate containment to avoid environmental contamination. | | | | |
| Not suitable | Prolonged exposure to elevated temperature | | | | |
| Section 8. Exposure controls/personal protection | | | | | |
| Control parameters | | | | | |
| Occupational exposure limits | | | | | |

None.

| Appropriate engineering controls | Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible. | | | | |
|-------------------------------------|---|--|--|--|--|
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. | | | | |
| Individual protection measures | | | | | |
| Hygiene measures | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | | | | |
| Eye/face protection | Safety glasses with side shields. | | | | |
| Skin protection | | | | | |
| Hand protection | Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. | | | | |

Section 8. Exposure controls/personal protection

| | • • |
|-------------------------------|---|
| Body protection | Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. |
| <u>Respiratory protection</u> | In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. |

Section 9. Physical and chemical properties

| <u>Appearance</u> | |
|--|---|
| Physical state | Liquid. |
| Colour | Amber. |
| Odour | Not available. |
| Odour threshold | Not available. |
| рН | Not available. |
| Melting point | Not available. |
| Boiling point | Not available. |
| Flash point | Open cup: >200°C (>392°F) [Cleveland.] |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. Based on - Physical state |
| Lower and upper explosive (flammable) limits | Not available. |
| Vapour pressure | Not available. |
| Vapour density | Not available. |
| Relative density | Not available. |
| Density | <1000 kg/m³ (<1 g/cm³) at 15°C |
| Solubility | insoluble in water. |
| Partition coefficient: n- octanol/water | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Kinematic: 40 mm²/s (40 cSt) at 40°C Kinematic: 8.1 mm²/s (8.1 cSt) at 100°C |

Section 10. Stability and reactivity

| Reactivity | No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information. |
|------------------------------------|--|
| Chemical stability | The product is stable. |
| Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur. |
| Product name Castrol Trans | |

| Product name | Castrol Transm | nax Manual V 75W-80 | Pro | duct code | 469686-DE01 | Page: 5/9 |
|--------------|----------------|---------------------|------------|-----------|-------------|-----------|
| Version 3.01 | Date of issue | 11/24/2020. | Format Rus | sia | Language | ENGLISH |
| | | | Rus | sia | | (ENGLISH) |

Section 10. Stability and reactivity

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Specific target organ toxicity (single exposure)

| | Route of exposure | Target organs |
|------------|-------------------|---|
| Category 3 | Not applicable. | Respiratory tract irritation |
| | | |
| Category | Route of exposure | Target organs |
| Category 2 | Not determined | Not determined |
| · | Category | Category 3 Not applicable. Category Route of exposure |

Aspiration hazard

| Name | Result |
|---|--------------------------------|
| 1-Decene, homopolymer, hydrogenated | ASPIRATION HAZARD - Category 1 |
| Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | ASPIRATION HAZARD - Category 1 |
| Base oil - unspecified | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ASPIRATION HAZARD - Category 1 |
| Alkenyl amine | ASPIRATION HAZARD - Category 1 |
| dec-1-ene | ASPIRATION HAZARD - Category 1 |

Information on likely routes Routes of entry anticipated: Dermal, Inhalation.

of exposure

| Potential acute health effects | |
|--------------------------------|--|
| Eye contact | No known significant effects or critical hazards. |
| Inhalation | Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure. |
| Skin contact | Defatting to the skin. May cause skin dryness and irritation. |
| Ingestion | No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

| Eye contact | No specific data. |
|--------------|--|
| Inhalation | May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. |
| Skin contact | Adverse symptoms may include the following: irritation dryness cracking |
| Ingestion | No specific data. |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

| Product name Castrol Transmax Manual V 75W-80 | Product code | 469686-DE01 Page: 6/9 |
|---|---------------|-----------------------|
| Version 3.01 Date of issue 11/24/2020. | Format Russia | Language ENGLISH |
| | Russia | (ENGLISH) |

Section 11. Toxicological information

| | - |
|------------------------------|--|
| Inhalation | Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. |
| Skin contact | Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis. |
| Ingestion | Ingestion of large quantities may cause nausea and diarrhoea. |
| Potential chronic health eff | <u>ects</u> |
| General | No known significant effects or critical hazards. |
| Carcinogenicity | No known significant effects or critical hazards. |
| Mutagenicity | No known significant effects or critical hazards. |
| Teratogenicity | No known significant effects or critical hazards. |
| Developmental effects | No known significant effects or critical hazards. |
| Fertility effects | No known significant effects or critical hazards. |

Numerical measures of toxicity

| Acute toxicity estimates | | |
|--------------------------|----------------|--|
| Route | ATE value | |
| Oral | 19047.62 mg/kg | |

Section 12. Ecological information

Environmental effects

This material is harmful to aquatic life with long lasting effects.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

| <u>Mobility in soil</u> Mobility | Spillages may penetrate the soil causing ground water contamination. |
|-------------------------------------|---|
| Other ecological information | Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired. |

Section 13. Disposal considerations

| Disposal methods | The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
|------------------|---|
|------------------|---|

| Product name | Castrol Transm | ax Manual V 75W-80 | Product code | 469686-DE01 | Page: 7/9 |
|--------------|----------------|--------------------|---------------|-------------|-----------|
| Version 3.01 | Date of issue | 11/24/2020. | Format Russia | Language | ENGLISH |
| | | | Russia | | (ENGLISH) |

Section 14. Transport information

| | IMDG | IATA |
|----------------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. |
| UN proper shipping name | - | - |
| Transport hazard class(es) | - | - |
| Packing group | - | - |
| Environmental hazards | No. | No. |
| Additional information | - | - |

Special precautions for user Not a

Not available.

Section 15. Regulatory information

Regulation according to other foreign laws

| REACH Status | The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH. |
|---|---|
| United States inventory (TSCA 8b) | All components are active or exempted. |
| Australia inventory (AICS) | All components are listed or exempted. |
| Canada inventory | All components are listed or exempted. |
| China inventory (IECSC) | All components are listed or exempted. |
| Japan inventory (ENCS) | All components are listed or exempted. |
| Korea inventory (KECI) | All components are listed or exempted. |
| Philippines inventory (PICCS) | All components are listed or exempted. |
| Taiwan Chemical Substances Inventory (TCSI) | All components are listed or exempted. |

Section 16. Other information

| <u>History</u> | |
|--------------------------------|---------------------|
| Date of printing | 11/24/2020 |
| Date of issue/Date of revision | 11/24/2020 |
| Date of previous issue | 10/22/2020 |
| Version | 3.01 |
| Prepared by | Product Stewardship |

Product name Castrol Transmax Manual V 75W-80 Version 3.01 Date of issue 11/24/2020. Product code469686-DE01Page: 8/9Format RussiaLanguageENGLISHRussia(ENGLISH)

Section 16. Other information

| Key to abbreviations | ATE = Acute Toxicity Estimate |
|----------------------|---|
| | BCF = Bioconcentration Factor |
| | GHS = Globally Harmonized System of Classification and Labelling of Chemicals |
| | IATA = International Air Transport Association |
| | · · · · · · · · · · · · · · · · · · · |
| | IBC = Intermediate Bulk Container |
| | IMDG = International Maritime Dangerous Goods |
| | LogPow = logarithm of the octanol/water partition coefficient |
| | MARPOL = International Convention for the Prevention of Pollution From Ships, |
| | 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| | REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals |
| | Regulation [Regulation (EC) No. 1907/2006] |
| | UN = United Nations |
| | Varies = may contain one or more of the following 64741-88-4, 64741-89-5, |
| | |
| | 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, |
| | 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, |
| | 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, |
| | 72623-87-1 |
| References | Not available. |

V Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.