

Viscoplus for Oil

Description

Mono functional additive that stabilizes motor oil viscosity. Provides outstanding protection against mechanical and permanent shear losses in extreme conditions and prevents viscosity loss caused by frequent cold starts.



Properties

- minimizes viscosity loss
- optimum lubrication under all operating conditions
- fully compatible with mineral and synthetic oils
- reduces engine noise
- optimum oil pressure under all operating conditions
- reduces oil consumption
- improves piston ring seal
- reduces wear

Available pack sizes

300 ml Can sheet metal 20338
CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Color / appearance	orange clear
Density at 68 °F	0,89 g/cm ³ DIN 51757
Viscosity at 104 °F	299,6 mm ² /s ASTM D7042
Flash point	248 °F DIN ISO 2592
Pour point	5 °F DIN ISO 3016
Odor	characteristic
Form	liquid

Areas of application

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF).

Comment

Not suitable for use on motorbikes with wet clutches.

Application

Contents (300 ml) is sufficient for 3–5 Liters (0.8 gal. to 1.3 gal.) motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

Available pack sizes

300 ml Can sheet metal 20206
USA-EN