

## Gear-Oil Leak Stop

### Description

Regenerates rubber and plastic transmission seals such as shaft seals and prevents oil stains under the vehicle. Protects clutches from oil fouling and prevents incomplete lubrication and transmission damages that are caused by too low an oil level. Prevents polluting oil stains.



### Properties

- prevents oil leaks and pollution of the environment
- increases operational reliability
- optimum lubrication under all operating conditions
- avoids oil leaking onto clutches
- prevents oil loss
- simple to use
- remedies leaks at shrunken or porous seals
- miscible with all commercially available gear oils

### Technical data

Viscosity at 104 °F	642 mm <sup>2</sup> /s DIN 51562
Viscosity index	101 DIN ISO 2909
Flash point	150 °F DIN ISO 2592
Pour point	-16 °F DIN ISO 3016
Color number (ASTM)	3,5 DIN ISO 2049
Base	combination of additives
Color / appearance	blue
Density at 68 °F	0,92 g/ml
Odor	characteristic
Form	liquid

### Areas of application

For manual transmissions, auxiliary and differentials.

**Not suitable for the use in transmissions and differentials with a wet-clutch.**

### Application

One tube is sufficient for 0.26 gal (1 l) of gear oil. The product can be added at any time. For best results, add every time the oil is changed.

**Our information is based on thorough research and may be considered reliable, although not legally binding.**