



Shell Ensis DW 1262

Medium term rust preventive with dewatering properties

Shell Ensis DW 1262 is medium-term rust preventive oil, which leaves a waxy film with dewatering properties.

Applications

Shell Ensis DW 1262 is **medium term rust protective** suitable for metal surfaces likely to corrode in storage or use.

Shell Ensis DW 1262 is a **water-displacing solvent-based** rust inhibitor that leaves temporary **waxy protective film** on metal surfaces. The product protects metal parts from the damaging effects of moisture, air, detergents & other contaminants.

Shell Ensis DW 1262 can be applied by dipping or spraying.

Characteristics

After the evaporation of the solvent Shell Ensis DW 1262 leaves a waxy film on surfaces. Shell Ensis DW 1262 is easily removed with aqueous alkaline cleaners or solvents.

It is premium quality dewatering type rust preventives with good coverage. Effective in neutralising finger prints. Resists cracking & peeling.

Use Shell Ensis DW 1262 where you require excellent covering capacity and excellent medium-term protection.

Duration of Protection

Indoors:	12 months
Covered Outdoors	3 months
Outdoors	Not recommended

Storage

The product should be stored inside (5 – 40 °C) for no more than 2 years and be protected from freezing.

Health & Safety

Shell Ensis DW 1262 is unlikely to present any significant health or safety hazard when properly used in recommended application and good standards of industrial and personal hygiene are maintained.

Typical Physical Characteristics

	Shell Ensis DW 1262
Classification ISO 6743-8	ISO-L-RFF
Appearance	Clear yellow
Density at 15 °C (kg/m ³) (DIN EN ISO 12185)	814
Kinematic Viscosity at 20 °C (mm ² /s) (ASTM D 7042)	2,9
Flash point (°C) (ASTM D 93)	65
Film thickness (µm)	2,8

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.