



# Hyundai Gear 75W-85W

*High quality gearbox oils*

Hyundai Gear 75W-85W is an initial fill high quality automotive gear lubricant especially formulated for Hyundai vehicles.

## DESIGNED TO MEET CHALLENGES

### Performance, Features & Benefits

- **Comprehensive components**

Specially selected additives impart good antiwear, oxidation stability and anti-rust characteristics.

### Main Applications

- **Manual gearboxes**

Hyundai Gear 75W-85W is essentially for the lubrication of manual gearboxes of passenger cars and commercial vehicles of Hyundai brand operating under high speed/low torque and low speed/high torque conditions. Suitable for gearboxes fitted with synchromesh.

- **Rear axles**

Suitable for applications presenting conditions of medium severity, such as light duty commercial vehicles and passenger cars. Not suitable for heavy duty hypoid axles.

### Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

### Typical Physical Characteristics

Properties			Method	Hyundai Gear
SAE Viscosity grade			SAE J 306	75W-85W
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ISO 3104	66
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ISO 3104	12
Viscosity Index			ISO 2909	170
Density	@15°C	kg/m <sup>3</sup>	ISO 12185	893
Flash Point COC	°C		ISO 2592	180
Pour Point	°C		ISO 3016	-40

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

- **Health and Safety**

Hyundai Gear is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from [www.epc.shell.com](http://www.epc.shell.com)

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.